



- 1: Power line Three-color lines connected with U, V and W phases/ yellow and green wires grounded
Temperature controlline 110°C thermistor two-phase connected with the temperature-control protector
- 2: Cooling water feed Pump lift 8m
- 3: Pole change and dust removal pressure
0.2-0.3Mpa (6/4 hoses)
- 4: Quantity of proximity switches Pole hanging and pole discharge NPN (normally open) N.O.
Wiring method of the proximity switch Brown wire connected with +24VDC blue wire connected with 0VDC
Signal load end connected with +24VDC/the other end connected with the black wire
- 5: Air seal pressure 0.1-0.2Mpa (4/2 hoses)
- 6: Cooling water yielding (2 and 6 ends terminated with 8/6 hoses)
- 7: Air inlet pressure of the cylinder 0.65Mpa (6/4 hoses)

PTC single-core thermistor parameter	
DC power supply	Maximum DC25V/100mA
-20~25℃	≤300Ω
≤90℃	≤750Ω
105℃	≤1650Ω
110℃	Rated operating temperature
115℃	≥3990Ω
≥125℃	≥12KΩ
≤160℃	Maximum storage temperature

Special warning:

1. The electric main shaft shall be installed at the clamped position; otherwise the bearing will be easily damaged!
2. The main shaft shall entirely stop before the tool changing. The manual tool changing button shall not act during the rotation of the shaft; otherwise it will easily result in the seizure of the shaft!
3. The compressed air shall be clean and dry, and the filter accuracy shall be 0.1micron! Air seal is normally open. It is recommended to use the two-level filter, and the filter accuracy is 0.5 micron/ 0.1 micron respectively. The air filter is installed with the self-discharge device.

									Outline diagram
Marks	Number of places	Zoning	Modified document number	Signature	Date	Phase mark	Weight	Scale	
Designed by			Standardized by						
Reviewed by									
Processed by			Approved by			Total page(s)	Page		
									SPAW-2.2